



THROUGH-TYPE TERMINAL THERMOPL. SCREW
TERMINAL ON BOTH ENDS SINGLE TERM.,BLACK,
6.5MM, 4

Similar to image

Technical data:

Operating current / rated value	A	32
Operating voltage / rated value	V	800
Mounting type		DIN rail 35 mm
Combustibility class acc. to UL 94		V2
Material / of the insulating body		Thermoplast
Design of the electrical connection		
• 1		screw-type terminal
• 2		screw-type terminal
Design tested acc. to type of protection / EEx e		No
Product component / required / connection plate		No
Number of terminal levels		1
Number of terminal points / per terminal level		2
Design of terminal / terminal levels linked internally		No
Terminal contact spacing	mm	6.5
Position / of terminal		lateral
Height / with lowest-profile installation	mm	26
Color		black
Length	mm	41

Ambient temperature • during operating	°C	-25 ... +55
Conductor cross-section that can be connected • solid • multibrin • finely stranded • without wire end processing • with wire end processing	mm ²	4 ... 4
	mm ²	4 ... 4
	mm ²	4 ... 4
	mm ²	4 ... 4

Certificates/approvals:

General Product Approval



Shipping Approval

other



[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA1011-1BG24>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-1BG24/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1BG24

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jun 30, 2014