



FUSE TERMINAL SCREW CONNECTION FOR G FUSE LINK 5X20MM AND 5X25MM WITH LED 48V

Similar to image

Technical data:		
Mounting type		DIN rail 35 mm
Length	mm	57
Color		miscellaneous
Terminal contact spacing	mm	10
Design of fuse holder		pluggable
Design of the fuse link		glass fuse 5x25 mm
Height / with lowest-profile installation	mm	42
Type of voltage / for supply of the fault indicator		AC/DC
Type of lamp / as fault indicator		LED
Number of terminal levels		1
Combustibility class acc. to UL 94		Other
Insulation material		thermoplastic
Position / of terminal		lateral
Product component / required / connection plate		No
Tension d'alimentation / pour affichage de défauts / maximum	V	48
Operating voltage / rated value	V	250
Operating current / rated value	A	6.3
Design of the electrical connection		

• 1		screw-type terminal
• 2		screw-type terminal
Conductor cross-section that can be connected		
• solid	mm ²	1 ... 1
• finely stranded		
• with wire end processing	mm ²	0.75 ... 1.5

Certificates/approvals:

General Product Approval



other

[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA1011-1SF14>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-1SF14/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF14

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014