



| Appearance                                       |                 |
|--------------------------------------------------|-----------------|
| Color                                            | miscellaneous   |
| Product feature / Touch protection               | No              |
| Product feature / insulated                      | No              |
| accessories                                      | cross connector |
| Number of bridged terminals                      | 2               |
| Mechanical Design                                |                 |
| Mounting type                                    | screwable       |
| Contact spacing                                  | 6 mm            |
| Net weight                                       | 3 g             |
| Certificates                                     |                 |
| Design tested acc. to type of protection / EEx e | No              |

| Declaration of<br>Conformity                                                                  | Test Certificates       | other                             |
|-----------------------------------------------------------------------------------------------|-------------------------|-----------------------------------|
| <br>EG-Konf. | <a href="#">sonstig</a> | <a href="#">Umweltbestätigung</a> |

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1885>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/8WA1885/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WA1885](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1885)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>