

SCREWDRIVER, LONG, PARTIALLY INSULATED,
GREEN W. SCREWDRIVER POINT 3.5X0.5,
E.G. F. OPERATING SPRING-L. TERMINAL



Similar to image

Technical data:

Longueur / de la tige de tournevis	mm	175
Shape of the screwdriver tip		Pozidriv PZ
Product property / electrically isolated		Yes
Product feature / clamp		No
Product property / protective insulation to 1000 V		No
Product feature / Hex on screwdriver shank		No
Design of screwdriver shaft		straight
Design of handle		1-component
Dimension de la tête de tournevis		others
Design of the screwdriver / precision design		No

Certificates/approvals:

General Product Approval other



[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/maill>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA2880/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA2880

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Apr 9, 2012