




TERMINAL FOR MOUNTING RAIL MOLDED
THERMOPLASTIC W. SCREW/PLUG CONNECTION

Similar to image

Technical data:

Design tested acc. to type of protection / EEx e		No
Component type		others
Length	mm	27
Height / with lowest-profile installation	mm	34
Mounting type		DIN rail 35 mm
Number of terminal levels		2
Number of terminal points / per terminal level		2
Design of terminal / terminal levels linked internally		No
Operating voltage / rated value	V	690
Operating current / rated value	A	24
Combustibility class acc. to UL 94		others
Color		beige
Insulation material		others
Terminal contact spacing	mm	7.5
Position / of terminal		top
Product component / required / connection plate		No
Design of the electrical connection		
• 1		screw-type terminal

• 2

Conductor cross-section that can be connected

- solid
- multibrin
- finely stranded
 - with wire end processing
 - without wire end processing

screw-type terminal

mm ²	0.5 ... 6
mm ²	0.5 ... 4
mm ²	0.5 ... 4
mm ²	0.5 ... 0.5

Certificates/approvals:

General Product Approval

**Declaration of
Conformity**

other



[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA9200>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA9200/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA9200

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014