



BUILT-IN LUMINAIRE ROTATING BEACON,
24V, GREEN

General technical details:

product designation		rotating light
Consumed current	mA	70
Type of voltage • of the operating voltage • of the supply voltage / of the fluorescent material		AC/DC AC/DC
Operating frequency • 1 / rated value	Hz	50
Operating voltage • 1 / for DC / rated value • 1 / at 50 Hz / for AC / rated value	V V	24 24
Supply voltage / 1 / of the fluorescent material • at 50 Hz / for AC / rated value • for DC / rated value	V V	24 24
Revolution	1/min	120
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		H P

Mechanical design:

Product component / fluorescent materials		Yes
Type of mounting		screw fixing
Material / of the enclosure		thermoplast
Color / of the lens		green
External diameter / of the signal column element	mm	70

Lamp:

Design of the light		lights with integrated LEDs
Nature of fluorescent material		LED

Ambient conditions:

Ambient temperature		
• during operating	°C	-20 ... +60
Protection class IP		IP65
Depth	mm	75
Height	mm	96.5
Width	mm	75

Certificates/approvals:

General Product Approval	EMC	Declaration of Conformity
 GOST	 UL	 C-TICK
		 EG-Konf.

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WD5320-5DC/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD5320-5DC



last change:

Jan 23, 2013