

TAB TERMINAL WITH BOLT CONNECTION,
SECTION: 0 - 25 MM2, AWG: 6 - 4,
WIDTH: 26 MM, COLOR: GRAY



Similar to image

Technical data:		
Operating current / rated value	A	101
Operating voltage / rated value	V	1,000
Mounting type		DIN rail 35 mm
Combustibility class acc. to UL 94		HB
Material / of the insulating body		Other
Design of the electrical connection		
• 1		bolt connection
• 2		bolt connection
Design tested acc. to type of protection / EEx e		No
Product component / required / connection plate		No
Number of terminal levels		2
Number of terminal points / per terminal level		1
Design of terminal / terminal levels linked internally		No
Terminal contact spacing	mm	23
Position / of terminal		top
Height / with lowest-profile installation	mm	53
Color		grey
Length	mm	88

Ambient temperature • during operating	°C	-25 ... +55
Conductor cross-section that can be connected • solid • multibrin • finely stranded • without wire end processing • with wire end processing	mm ²	25 ... 25
	mm ²	25 ... 25
	mm ²	25 ... 25
	mm ²	25 ... 25

Certificates/approvals:

General Product Approval

Declaration of Conformity

Shipping Approval



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH1060-0AL00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH1060-0AL00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH1060-0AL00

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 4, 2014