

TAB TERMINAL WITH BOLT CONNECTION, SECTION: 0 - 150
MM2, WIDTH: 46 MM, COLOR: GRAY



Model

Design of terminal / Terminal levels internally linked No

General technical data

Terminal contact spacing 46 mm

Protection class

Combustibility class acc. to UL 94 HB

Main circuit

Operating voltage / rated value 1 000 V

Operating current / rated value 309 A

Appearance

Color grey

Product details

Product component / required / connection plate No

Number

Number of terminal levels 2

Number of terminal points / per terminal level 1

Connections

Connectable conductor cross-section / stranded	
• minimum	150 mm ²
• maximum	150 mm ²
Connectable conductor cross-section	
• solid	
— minimum	150 mm ²
— maximum	150 mm ²
• finely stranded	
— with core end processing / minimum	150 mm ²
— with core end processing / maximum	150 mm ²
— without core end processing / minimum	150 mm ²
— without core end processing / maximum	150 mm ²
Type of electrical connection	
• 1	bolt connection
• 2	bolt connection
Position / of the terminal	top

Mechanical Design

Height / with lowest-profile installation	56 mm
Length	110 mm
Mounting type	DIN rail 35 mm
Net weight	333 g
Material / of the insulating body	Other

Environmental conditions

Ambient temperature	
• during operation / minimum	-25 °C
• during operation / maximum	55 °C

Certificates

Design tested acc. to type of protection / EEx e	No		
General Product Approval	Declaration of Conformity	other	



[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH1060-0AS00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH1060-0AS00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH1060-0AS00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>