


PE TERMINAL WITH SPRING CONNECTION,
4 CONNECT. POINTS,
SECTION: 0.14 - 1.5 MM², WIDTH: 4, . MM,
COLOR:GREEN-YEL.



Similar to image

Technical data:

Mounting type		DIN rail 35 mm
Length	mm	72
Color		green-yellow
Height / with lowest-profile installation	mm	36.5
Number of terminal levels		1
Number of terminal points / per terminal level		4
Product feature / PEN function		No
Combustibility class acc. to UL 94		V0
Terminal contact spacing	mm	4.2
Position / of terminal		top
Product component / required / connection plate		No
Ambient temperature		
• during operating	°C	-25 ... +35
Design of the electrical connection		
• 1		spring-loaded terminal
• 2		spring-loaded terminal
Conductor cross-section that can be connected		
• solid	mm ²	0.14 ... 1.5

- multibrin
- finely stranded
 - with wire end processing
 - without wire end processing

mm ²	0.14 ... 1.5
mm ²	0.14 ... 1.5
mm ²	1.5 ... 1.5

Certificates/approvals:

General Product Approval



Shipping Approval



GL



LRS

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH2004-0CE07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH2004-0CE07/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2004-0CE07

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014