


HYBRID FEED-THROUGH TERMINAL SCREW AND 2X
SPRING CONNECTION SECTION: 0.08 - 4 MM²,
WIDTH: 5.2 MM, COLOR: BLUE



Similar to image

Technical data:		
Operating current / rated value	A	32
Operating voltage / rated value	V	800
Mounting type		DIN rail 35 mm
Combustibility class acc. to UL 94		V0
Material / of the insulating body		Other
Design of the electrical connection		
• 1		spring-loaded terminal
• 2		screw-type terminal
Design tested acc. to type of protection / EEx e		No
Product component / required / connection plate		No
Number of terminal levels		1
Number of terminal points / per terminal level		3
Design of terminal / terminal levels linked internally		No
Terminal contact spacing	mm	6.2
Position / of terminal		top
Color		blue
Ambient temperature		
• during operating	°C	-25 ... +55

Conductor cross-section that can be connected

- solid
- multibrin
- finely stranded
 - without wire end processing
 - with wire end processing

mm² 6 ... 6mm² 6 ... 6mm² 4 ... 4mm² 4 ... 4**Certificates/approvals:****General Product Approval****Declaration of Conformity****Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH2103-2BG01>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/8WH2103-2BG01/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2103-2BG01**CAX-Online-Generator**<http://www.siemens.com/cax>**last change:**

Aug 4, 2014