

HYBRID PE TERMINAL, 3 CONNECT. POINTS,  
WITH QUICK AND SCREW CONNECTION,  
SECTION: 0.25 - 1.5 MM<sup>2</sup>, WIDTH:5.2 MM,  
COLOR: GREEN-YEL.



Similar to image

**Technical data:**

<b>Mounting type</b>		DIN rail 35 mm
<b>Length</b>	mm	76.4
<b>Color</b>		green-yellow
<b>Height / with lowest-profile installation</b>	mm	42.8
<b>Number of terminal levels</b>		1
<b>Number of terminal points / per terminal level</b>		3
<b>Product feature / PEN function</b>		No
<b>Combustibility class acc. to UL 94</b>		V0
<b>Terminal contact spacing</b>	mm	5.2
<b>Position / of terminal</b>		top
<b>Product component / required / connection plate</b>		No
<b>Ambient temperature</b>		
• during operating	°C	-25 ... +35
<b>Design of the electrical connection</b>		
• 1		screw-type terminal
• 2		insulation piercing connection
<b>Conductor cross-section that can be connected</b>		
• solid	mm <sup>2</sup>	0.25 ... 4

- multibrin
- finely stranded
  - with wire end processing
  - without wire end processing

mm <sup>2</sup>	0.5 ... 2.5
mm <sup>2</sup>	0.5 ... 2.5
mm <sup>2</sup>	2.5 ... 2.5

### Certificates/approvals:

#### General Product Approval



#### Declaration of Conformity



### Further information:

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH3103-3DE07>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH3103-3DE07/all>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH3103-3DE07](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH3103-3DE07)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014