


PE TERMINAL,
PLUG CONNECTION ON BOTH ENDS,
SECTION 0.08 - 2.5 MM², WIDTH: 5.2 MM,
COLOR:GREEN-YEL.



Similar to image

Technical data:		
Mounting type		DIN rail 35 mm
Length	mm	48.5
Color		green-yellow
Height / with lowest-profile installation	mm	36.5
Number of terminal levels		1
Number of terminal points / per terminal level		2
Product feature / PEN function		No
Combustibility class acc. to UL 94		V0
Terminal contact spacing	mm	5.2
Position / of terminal		top
Product component / required / connection plate		No
Ambient temperature		
• during operating	°C	-25 ... +35
Design of the electrical connection		
• 1		connector
• 2		connector
Conductor cross-section that can be connected		
• solid	mm ²	0.25 ... 2.5

- multibrin
- finely stranded
 - with wire end processing
 - without wire end processing

mm ²	0.25 ... 2.5
mm ²	0.25 ... 2.5
mm ²	2.5 ... 2.5

Certificates/approvals:

General Product Approval



GOST



UL

Declaration of Conformity



EG-Konf.

Shipping Approval



LRS

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH5000-0CF07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH5000-0CF07/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH5000-0CF07

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014