

FUSE-TERMINAL BLOCK 5X20MM 4 MM2,
6,2 MM WIDTH SCHWARZ 250V LED

Technical data:

Mounting type		DIN rail 35 mm
Length	mm	56
Color		black
Terminal contact spacing	mm	6.2
Design of fuse holder		pluggable
Design of the fuse link		glass fuse 5x20 mm
Height / with lowest-profile installation	mm	62.5
Type of voltage / for supply of the fault indicator		AC/DC
Type of lamp / as fault indicator		LED
Number of terminal levels		1
Combustibility class acc. to UL 94		V0
Insulation material		thermoplastic
Position / of terminal		top
Product component / required / connection plate		Yes
Tension d'alimentation / pour affichage de défauts / maximum	V	250
Operating voltage / rated value	V	500
Operating current / rated value	A	6.3
Conductor cross-section that can be connected		
• solid	mm ²	0.2 ... 6
• multibrin	mm ²	0.25 ... 4
• finely stranded		
• with wire end processing	mm ²	0.25 ... 4
• without wire end processing	mm ²	0.2 ... 4

Certificates/approvals:

General Product Approval



Declaration of Conformity

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH6000-1MG88>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH6000-1MG88/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH6000-1MG88

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014