

PE-INSTA-TERMINALS 2,5 MM²,
5,2 MM WIDTH GREEN-YELLOW



Similar to image

Technical data:

Mounting type		DIN rail 35 mm
Combustibility class acc. to UL 94		V0
Material / of the insulating body		Thermoplast
Design of the electrical connection		
• 1		plug terminal connection
• 2		plug terminal connection
Design tested acc. to type of protection / EEx e		No
Product component / required / connection plate		Yes
Number of terminal levels		1
Number of terminal points / per terminal level		2
Design of terminal / terminal levels linked internally		No
Terminal contact spacing	mm	5.2
Position / of terminal		top
Height / with lowest-profile installation	mm	43
Color		Green-yellow
Length	mm	59.5
Ambient temperature		
• during operating	/ °C	55

Conductor cross-section that can be connected

- solid
- finely stranded
 - without wire end processing
 - with wire end processing

mm²

0.2 ... 4

mm²

0.2 ... 2.5

mm²

0.2 ... 2.5

Certificates/approvals:**General Product Approval****Declaration of Conformity****Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH6001-OCF07>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/8WH6001-OCF07/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH6001-OCF07**CAX-Online-Generator**<http://www.siemens.com/cax>

last change:

Jul 28, 2014