

REDUCING JUMPER, TO CONNECT SPRING CONNECTIONS 6 MM2 WITH SPRING TERMINALS 2.5 MM2 OR 4 MM2, SIEMENS COLOR



Operating current	
• for single-sided supply	40 A
• for center supply	56 A
Main circuit	
Operating current / rated value	40 A
Appearance	
Color	miscellaneous
Product feature / Touch protection	Yes
Product feature / insulated	Yes
Number of bridged terminals	1
Mechanical Design	
Mounting type	pluggable
Contact spacing	6 mm
Net weight	4 g
Certificates	
Design tested acc. to type of protection / EEx e	No

**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH9020-0FC10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH9020-0FC10/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9020-0FC10

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>