



INSERTABLE JUMPER, 3-POLE,
FULLY INSULATED,
INSERTED IN LOCKING SLEEVE AND LATCHED FOR 150
MM2 TERMINALS

Similar to image

Technical data:

Mounting type		others
Color		grey
Design tested acc. to type of protection / EEx e		No
Product equipment / touch-protection		Yes
Contact spacing	mm	150
Accessories		insertion bridge
Product property / electrically isolated		Yes
Number of bridged terminals		3
Operating current / rated value	A	232

Certificates/approvals:

General Product Approval

Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH9020-3DA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH9020-3DA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9020-3DA00

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 4, 2014