

INSERTABLE PROFILE,
FOR 50MM² TERMINALS,
COMPENSATES PRISMATIC SLEEVE BASES WHEN
STRIP LINES ARE USED



Similar to image

Technical data:		
Mounting type		others
Color		miscellaneous
Height / with lowest-profile installation	mm	81.5
Number of terminal points / per terminal level		0
Combustibility class acc. to UL 94		others
Position / of terminal		lateral
Product component / required / connection plate		No
Ambient temperature		
• during operating	°C	-25 ... +35
Design of the electrical connection		
• 1		Miscellaneous
• 2		Miscellaneous
Conductor cross-section that can be connected		
• finely stranded		
• with wire end processing	mm ²	16 ... 50

Certificates/approvals:

**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH9020-3MA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH9020-3MA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9020-3MA00

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014