



Similar to image

PICK-OFF TERM. SECTION 10MM² FOR HIGH-CURRENT TERMINALS,
WITH 150 - 240 MM², FULLY ISOLATED,
ALLOWS A VOLTAGE TAP UP TO A NOM. VOLTAGE OF 1000 V,
GRAY

Technical data:

Operating current / rated value	A	57
Mounting type		others
Combustibility class acc. to UL 94		others
Material / of the insulating body		Other
Design of the electrical connection		
• 1		screw-type terminal
• 2		without
Product component / required / connection plate		No
Number of terminal levels		1
Number of terminal points / per terminal level		1
Design of terminal / terminal levels linked internally		No
Position / of terminal		others
Color		grey
Ambient temperature		
• during operating	°C	-25 ... +55
Conductor cross-section that can be connected		
• finely stranded		
• with wire end processing	mm ²	150 ... 240

Certificates/approvals:

General Product Approval



Declaration of Conformity

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH9120-0CA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH9120-0CA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9120-0CA00

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 4, 2014