



Shield terminal, for shield attachment on busbars, diameter 3-20 mm

terminal contact spacing		24 mm
Connections		
connectable cable cross-section		
• minimum		3 mm
• maximum		20 mm
type of electrical connection		screw terminal
Mechanical Design		
height		75 mm
fastening method		busbar
Approvals Certificates		
General Product Approval	other	Environment



[Confirmation](#)

[Environmental Con-
firmations](#)

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH9130-0NA00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/8WH9130-0NA00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9130-0NA00
CAX-Online-Generator http://www.siemens.com/cax
Tender specifications http://www.siemens.com/specifications

last modified:

5/9/2025

