Product datasheet Characteristics

9001KP7W9 PILOT LIGHT 240VAC 30MM TYPE K +OPTIONS



Price*: 69.23 GBP



Commercial status

Discontinued: 07 April 2020

Main

		4
Range of product	Harmony 9001K	- 0
Product or component type	Pilot light	
Device short name	K	

Complementary

Bezel material	Chromium plated metal	. <u>.</u>
Mounting diameter	30 mm	
Lens type	Domed plastic	
Cap/Operator or lens colour	White	
Light source	incandescent	-
Bulb base	BA 9s	
Light block supply	Via transformer 240 V AC 50/60 Hz Via integral transformer 220 V AC 50/60 Hz	
Connections - terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² conforming to IEC 60947-1	
Shape of screw head	Round	
Operating position	Any position	
[Us] rated supply voltage	220240 V AC	
Operating mode	Normal	
Device presentation	Complete product	

Environment

Product certifications	CE UL listed file E42259 CCN NKCR CSA LR25490 class 3211 03
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months