## **Product datasheet** Characteristics

# 9001KT1R9 PILOT LIGHT 120VAC 30MM TYPE K +OPTIONS





#### Main

	i de la companya de
Harmony 9001K	
Pilot light	1
К	
	<b>′</b>

### Complementary

Bezel material	Chromium plated metal	•
Mounting diameter	30 mm	
Lens type	Domed plastic	
Cap/Operator or lens colour	Red	
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz	-
Shape of screw head	Round	
Operating mode	Push-to-test	

#### Environment

Product certifications	CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR CE	
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	

### Offer Sustainability

Onor Odolamability		-
Sustainable offer status	Green Premium product	ي.
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	

Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months