Product datasheet Characteristics

9001SK1L 30MM ILLUM PUSH BUTTON TRANSFORMER 120V





Main

Mani		
Range of product	Harmony 9001SK	
Product or component type	Push-button	
Device short name	9001SK	
Bezel material	Black plastic	

Complementary

Mounting diameter	30 mm
Shape of signaling unit head	Octagonal
Light source	without
Contacts type and composition	Without contact block
Product certifications	CSA LR24590 class 3211 03 CE UL listed file E42259 CCN NKCR
IP degree of protection	IP64
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13

Offer Sustainability

Main		
Range of product	Harmony 9001SK	
Product or component type	Push-button	
Device short name	9001SK	
Bezel material	Black plastic	
Complementary		
Mounting diameter	30 mm	
Shape of signaling unit head	Octagonal	
Light source	without	
Contacts type and composition	Without contact block	
Product certifications	CSA LR24590 class 3211 03	
	CE UL listed file E42259 CCN NKCR	
IP degree of protection	IP64	
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	
Office Organization letter		
Offer Sustainability Sustainable offer status	Cross Promittes are dust	
	Green Premium product REACh Declaration	
REACh Regulation REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
EU KONS DIJECTIVE	EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
	Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	Harmony 9001SK Push-button 9001SK Black plastic 30 mm Octagonal without Without contact block CSA LR24590 class 3211 03 CE UL listed file E42259 CCN NKCR IP64 NEMA 1/2/3/3R/4/4X/6/12/13 Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes China RoHS declaration Product out of China RoHS scope. Substance declaration for your information Product Environmental Profile No need of specific recycling operations	

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		
Warranty	18 months	