



## Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Range of product          | Harmony 9001SK                       |
| Product or component type | Complete illuminated selector switch |
| Device short name         | 9001SK                               |
| Type of operator          | Stay put                             |
| Operator profile          | Long handle                          |

## Complementary

|                               |                                  |
|-------------------------------|----------------------------------|
| Bezel material                | Plastic                          |
| Mounting diameter             | 30 mm                            |
| Product weight                | 0.19 kg                          |
| Shape of signaling unit head  | Octagonal                        |
| Operator position information | 3 positions                      |
| Contacts type and composition | Without contact block            |
| Mechanical durability         | 500000 cycles                    |
| Light source                  | High luminosity LED              |
| Light block colour            | Amber                            |
| [Us] rated supply voltage     | 24 V AC/DC                       |
| Product compatibility         | 9001KA1, mounting on side 1 or 2 |

## Environment

|                                            |                                                                                                                |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Protective treatment                       | TC                                                                                                             |
| Ambient air temperature for storage        | -40...70 °C                                                                                                    |
| Ambient air temperature for operation      | -25...70 °C                                                                                                    |
| Class of protection against electric shock | Class II conforming to IEC 61140                                                                               |
| IP degree of protection                    | IP66 conforming to IEC 60529                                                                                   |
| NEMA degree of protection                  | NEMA 4X<br>NEMA 4<br>NEMA 3R<br>NEMA 3<br>NEMA 2<br>NEMA 13<br>NEMA 12<br>NEMA 1                               |
| Standards                                  | CSA C22-2 No 14<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508 |
| Product certifications                     | NEMA<br>UL 508                                                                                                 |
| Vibration resistance                       | 7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6                                                              |
| Shock resistance                           | 50 gn conforming to IEC 60068-2-27                                                                             |

Offer Sustainability

|                          |                                                                                                                          |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Not Green Premium product                                                                                                |
| RoHS                     | Compliant - since 0921 - Schneider Electric declaration of conformity <a href="#">download declaration of conformity</a> |