



Main

Product or component type	Pilot light
Lens type	Fresnel plastic
Light block supply	Full voltage 28 V Direct 24 V

Complementary

Bezel material	Plastic
Mounting diameter	30 mm
Shape of signaling unit head	Round
Cap/Operator or lens colour	Red
Light source	incandescent
Bulb base	BA 9s
[Us] rated supply voltage	24...28 V AC/DC
Operating position	Any position
Operating mode	Normal
CAD overall width	54 mm
CAD overall height	70 mm
CAD overall depth	42 mm
Device presentation	Complete product

Environment

Protective treatment	TC
IP degree of protection	IP66

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------