Product datasheet Characteristics

9001SKR1RH6 PUSHBUTTON 600VAC 10AMP 30MM SK +OPTIONS





Range of product	Harmony 9001SK	
Product or component type	Push-button	
Device short name	9001SK	
Type of operator	spring return	
Operator profile	Red flush	:
Operator additional information	Full guard in plastic	

Complementary

Bezel material	Plastic	
Mounting diameter	30 mm	
Contacts type and composition	1 NC	
Contact operation	Standard	
Mechanical durability	5000000 cycles	<u>-</u>
Device presentation	Complete product	

Environment

Standards	CSA C22.2 No 14 UL 508	
	JIS C 4520	
	JIS C 852 EN/IEC 60947-5-4	
	EN/IEC 60947-5-1 EN/IEC 60947-1	
IP degree of protection	IP66	. <u>.</u> E <u></u>
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	, in the state of

Offer Sustainability

		-1
Sustainable offer status	Green Premium product	

ractive compliance (Product out of EU RoHS legal scope) RoHS Declaration	
RoHS Declaration	
na RoHS declaration	
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
duct Environmental Profile	
No need of specific recycling operations	
product must be disposed on European Union markets following specific waste collection and er end up in rubbish bins	
1	

	<u> </u>	
Warranty	18 months	