Product datasheet Characteristics

9001SKR4R05H6 PUSHBUTTON 600VAC 10AMP 30MM SK +OPTIONS





TTT COLOR		ž
Range of product	Harmony 9001SK	
Product or component type	Push-button	1
Device short name	9001SK	

Complementary

Bezel material	Plastic	
Mounting diameter	30 mm	
Contact operation	Standard	
Mechanical durability	5000000 cycles	
Device presentation	Complete product	

Environment

		<u>8</u>
		iat ioi
		ab politic
		as S
		ojje r
Main		
Range of product	Harmony 9001SK	<u> </u>
Product or component type	Push-button	nci Do
Device short name	9001SK	20
		of the
Complementary		ioliity
Bezel material	Plastic	
Mounting diameter	30 mm	
Contact operation	Standard	
Mechanical durability	5000000 cycles	
Device presentation	Complete product	it it
		for d
Environment		pesn
Standards	JIS C 4520	 9 9
	CSA C22.2 No 14	to
	EN/IEC 60947-5-1 EN/IEC 60947-1	. <u>s.</u>
	UL 508	o.
	EN/IEC 60947-5-4	at a state of the
	JIS C 852	bstiti Tit
IP degree of protection	IP66	
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	ii ———————————————————————————————————
		ition is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications
Offer Sustainability		<u>o</u> <u>v</u>
Sustainable offer status	Green Premium product	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	F
Toxic heavy metal free	Yes	

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months