Product datasheet Characteristics

9001SKT1 30MM PILOT LIGHT PUSH TO TEST 110-120V





B 4		
N /I	211	٦
1 V I	an	ı

Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz	

Complementary

o op.ooy		
Bezel material	Plastic	
Mounting diameter	30 mm	
Shape of signaling unit head	Round	
Operating mode	Push-to-test	

Environment

Protective treatment	TC
IP degree of protection	IP66

Offer Sustainability

Main	
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz
Complementary	
Bezel material	Plastic
Mounting diameter	30 mm
Shape of signaling unit head	Round
Operating mode	Push-to-test
Environment	
Environment	
Protective treatment	TC
	TC IP66
Protective treatment	
Protective treatment IP degree of protection	
Protective treatment IP degree of protection Offer Sustainability	IP66
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status	
Protective treatment	IP66 Green Premium product
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation REACh free of SVHC	Green Premium product REACh Declaration
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive	Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope)
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive Toxic heavy metal free	Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive Toxic heavy metal free Mercury free	Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive Toxic heavy metal free Mercury free RoHS exemption information	Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes Yes
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive Toxic heavy metal free Mercury free RoHS exemption information China RoHS Regulation	Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes Yes Yes Yes China RoHS declaration
Protective treatment IP degree of protection Offer Sustainability Sustainable offer status REACh Regulation	Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes Yes Yes Yes Yes China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Warranty 18 months