

**M-D-STRIPAX AWG 26+28****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- Flexible and solid wire with PVC, Teflon (PTFE) and silicone insulation
- No damage to the wire thanks to specially shaped blade
- No splicing of individual wires
- Blade inserts are easy to replace
- All inserts fit one housing
- Guide bars in the blade cassettes facilitate correct positioning of the wire in the tool

**General ordering data**

|            |                                   |
|------------|-----------------------------------|
| Version    | Tools, Stripping and cutting tool |
| Order No.  | <a href="#">9003710000</a>        |
| Type       | M-D-STRIPAX AWG 26+28             |
| GTIN (EAN) | 4008190034184                     |
| Qty.       | 1 pc(s).                          |

**M-D-STRIPAX AWG 26+28****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 16 mm   | Depth (inches)  | 0.63 inch  |
| Height     | 135 mm  | Height (inches) | 5.315 inch |
| Net weight | 97.28 g | Weight          | 110 g      |
| Width      | 82 mm   | Width (inches)  | 3.228 inch |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Technical data**

|                        |                                           |
|------------------------|-------------------------------------------|
| Description of article | Stripping tool for up to AWG 24, for PTFE |
|------------------------|-------------------------------------------|

**Stripping tools**

|                           |                                  |                           |        |
|---------------------------|----------------------------------|---------------------------|--------|
| Cable type                | Conductor with custom insulation | Max. conductor diameter   | 0.5 mm |
| Min. conductor diameter   | 0.3 mm                           | Stripping length, max.    | 7 mm   |
| Stripping range AWG, max. | 24 AWG                           | Stripping range AWG, min. | 28 AWG |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002109    | ETIM 7.0    | EC002109    |
| ECLASS 9.0  | 21-04-37-06 | ECLASS 9.1  | 21-04-37-06 |
| ECLASS 10.0 | 21-04-37-06 | ECLASS 11.0 | 21-04-37-06 |

### M-D-STRIPAX AWG 26+28

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Example of use

