

**H1,0/14 GE BD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- Linked of wire-end ferrule strips (50 pcs.)
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                  |
|------------|--------------------------------------------------|
| Version    | Wire-end ferrule, insulated, 10 mm, 8 mm, yellow |
| Order No.  | <a href="#">9004320000</a>                       |
| Type       | H1,0/14 GE BD                                    |
| GTIN (EAN) | 4008190167523                                    |
| Qty.       | 500 pc(s).                                       |
| Packaging  | Reel packaged                                    |

## H1,0/14 GE BD

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.097 g |
|------------|---------|

## Technical data

|                        |                                       |         |           |
|------------------------|---------------------------------------|---------|-----------|
| Description of article | Strip of wire end ferrules,<br>yellow | Version | insulated |
|------------------------|---------------------------------------|---------|-----------|

## Wire-end ferrules

|                             |                   |                                            |            |
|-----------------------------|-------------------|--------------------------------------------|------------|
| Collar diameter (D2)        | 3 mm              | Colour code                                | Weidmüller |
| Conductor cross-section     | 1 mm <sup>2</sup> | Contact surface diameter (D1)              | 1.4 mm     |
| Contact surface length (L2) | 8 mm              | L1 in mm                                   | 14 mm      |
| Metal sleeve thickness (S1) | 0.15 mm           | Plastic collar thickness (S2)              | 0.25 mm    |
| Stripping length            | 10 mm             | Wire connection cross section AWG,<br>max. | AWG 17     |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |

**H1,0/14 GE BD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**