


**H0,5/14 ZH OR SV****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- in multipack bag (5 x 100 pcs.)
- Weidmüller colour code
- DIN colour code

**General ordering data**

|            |                                                              |
|------------|--------------------------------------------------------------|
| Version    | Wire-end ferrule, Twin wire-end ferrule, 11 mm, 8 mm, orange |
| Order No.  | <a href="#">9004440000</a>                                   |
| Type       | H0,5/14 ZH OR SV                                             |
| GTIN (EAN) | 4008190198473                                                |
| Qty.       | 500 pc(s).                                                   |
| Packaging  | Multipack bag                                                |

Creation date March 30, 2021 12:10:29 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## H0,5/14 ZH OR SV

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.124 g |
|------------|---------|

## Technical data

|                        |                               |         |                       |
|------------------------|-------------------------------|---------|-----------------------|
| Description of article | Twin wire end ferrule, orange | Version | Twin wire-end ferrule |
|------------------------|-------------------------------|---------|-----------------------|

## Wire-end ferrules

|                                         |            |                             |                     |
|-----------------------------------------|------------|-----------------------------|---------------------|
| Collar height (A)                       | 5 mm       | Collar width (B)            | 3 mm                |
| Colour code                             | Weidmüller | Conductor cross-section     | 0.5 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 1.4 mm     | Contact surface length (L2) | 8 mm                |
| L1 in mm                                | 14 mm      | Metal sleeve thickness (S1) | 0.15 mm             |
| Plastic collar thickness (S2)           | 0.3 mm     | Stripping length            | 11 mm               |
| Wire connection cross section AWG, max. | AWG 20     |                             |                     |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |

**H0,5/14 ZH OR SV****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**