# Product data sheet Characteristics

## 9007AO2B

Snap basic limit switch, 9007, plunger, NO, panel mount



Main	
Range of product	9007
Series name	Heavy duty
Product or component type	Snap basic limit switch
Device short name	9007AO/CO
Body type	Fixed

Complementar	У
--------------	---

head  c c ody eturn plunger plastic with thermoplastic end
c ody
c ody
ody
eturn plunger plastic with thermoplastic end
eturn plunger plastic with thermoplastic end
approach, 1 direction
oles for 6 binder head screw terminals (AWG 22AWG 14)
ch function: SPST-NO-DB
tion
intacts
20 V AC, A600 conforming to NEMA rating designation 30 V AC, A600 conforming to NEMA rating designation 240 V AC, A600 conforming to NEMA rating designation 120 V AC, A600 conforming to NEMA rating designation 600 V DC, Q600 conforming to NEMA rating designation 250 V DC, Q600 conforming to NEMA rating designation 25 V DC, Q600 conforming to NEMA rating designation
ollution degree 3) conforming to UL 508 for contact block onforming to CSA C22.2 No 14 for contact block
m
1
m

#### **Environment**

NEMA degree of protection	NEMA 1 conforming to Nema type 250
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20185 °F
Ambient air temperature for storage	-20185 °F

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.452 cm	
Package 1 Width	2.54 cm	
Package 1 Length	16.387 cm	
Package 1 Weight	45.359 g	

#### Offer Sustainability

Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

## Contractual warranty

Warranty	18 months