


**H35,0/39D R****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code

**General ordering data**

Version	Wire-end ferrule, insulated, 28 mm, 25 mm, red
Order No.	<a href="#">9019330000</a>
Type	H35,0/39D R
GTIN (EAN)	4008 190048365
Qty.	50 pc(s).
Packaging	loose

Creation date March 30, 2021 12:28:13 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**H35,0/39D R****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight 1.74 g

**Technical data**

Description of article	Wire end ferrule with plastic collar, red	Version	insulated
------------------------	---	---------	-----------

**Wire-end ferrules**

Collar diameter (D2)	12.7 mm	Colour code	DIN
Conductor cross-section	35 mm <sup>2</sup>	Contact surface diameter (D1)	8.3 mm
Contact surface length (L2)	25 mm	L1 in mm	39 mm
Metal sleeve thickness (S1)	0.2 mm	Military designation	T 20A 033 A
Plastic collar thickness (S2)	0.4 mm	Stripping length	28 mm
Wire connection cross section AWG, max.	AWG 2		

**Classifications**

ETIM 6.0	EC000005	ETIM 7.0	EC000005
ECLASS 9.0	27-40-02-01	ECLASS 9.1	27-40-02-01
ECLASS 10.0	27-40-02-01	ECLASS 11.0	27-40-02-01

**Approvals**

Approvals



ROHS	Conform
UL File Number Search	E499744

**Downloads**

Engineering Data	<a href="#">STEP</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
User Documentation	<a href="#">Technical information - EN</a> <a href="#">Technical information - DE</a>

**Data sheet**

**H35,0/39D R**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**

