

**H25,0/36T SW****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                  |
|------------|--------------------------------------------------|
| Version    | Wire-end ferrule, insulated, 24 mm, 22 mm, black |
| Order No.  | <a href="#">9021200000</a>                       |
| Type       | H25,0/36T SW                                     |
| GTIN (EAN) | 4008190055400                                    |
| Qty.       | 50 pc(s).                                        |
| Packaging  | loose                                            |

## H25,0/36T SW

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |        |
|------------|--------|
| Net weight | 1.44 g |
|------------|--------|

## Technical data

|                        |                                             |         |           |
|------------------------|---------------------------------------------|---------|-----------|
| Description of article | Wire end ferrule with plastic collar, black | Version | insulated |
|------------------------|---------------------------------------------|---------|-----------|

## Wire-end ferrules

|                                         |                    |                               |               |
|-----------------------------------------|--------------------|-------------------------------|---------------|
| Collar diameter (D2)                    | 11.2 mm            | Colour code                   | Telemecanique |
| Conductor cross-section                 | 25 mm <sup>2</sup> | Contact surface diameter (D1) | 7.3 mm        |
| Contact surface length (L2)             | 22 mm              | L1 in mm                      | 36 mm         |
| Metal sleeve thickness (S1)             | 0.2 mm             | Military designation          | T 20A 030 A   |
| Plastic collar thickness (S2)           | 0.4 mm             | Stripping length              | 24 mm         |
| Wire connection cross section AWG, max. | AWG 3              |                               |               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |

## H25,0/36T SW

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Drawing

