

## CRIMPFIX LZ

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

### General ordering data

|            |                                |
|------------|--------------------------------|
| Version    | Automatic stripper and crimper |
| Order No.  | <a href="#">9027310000</a>     |
| Type       | CRIMPFIX LZ                    |
| GTIN (EAN) | 4032248285440                  |
| Qty.       | 1 pc(s).                       |

**CRIMPFIX LZ****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |             |
|------------|----------|-----------------|-------------|
| Depth      | 330 mm   | Depth (inches)  | 12.992 inch |
| Height     | 460 mm   | Height (inches) | 18.11 inch  |
| Net weight | 36,000 g | Weight          | 31 kg       |
| Width      | 390 mm   | Width (inches)  | 15.354 inch |

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**PW65 maintenance - automatic stripping/crimping**

|                                       |                      |                                       |                                                          |
|---------------------------------------|----------------------|---------------------------------------|----------------------------------------------------------|
| Compressed-air connection             | 5 bar                | Consumables                           | Twin wire-end ferrules                                   |
| Crimping length                       | 8 mm                 | Drive                                 | Electropneumatic                                         |
| Electrical connection                 | 100-240 V / 50/65 Hz | Length of wire-end ferrule            | 14 mm                                                    |
| Pulse time                            | approx. 1 s          | Stripping range                       | 2 x 0.5 - 2 x 1.5 mm <sup>2</sup><br>(~ AWG 2x20 - 2x16) |
| Wire end ferrules cross-section, max. | 1.5 mm <sup>2</sup>  | Wire end ferrules cross-section, min. | 0.5 mm <sup>2</sup>                                      |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002778    | ETIM 7.0    | EC002778    |
| ECLASS 9.0  | 17-13-01-01 | ECLASS 9.1  | 17-13-01-01 |
| ECLASS 10.0 | 17-13-01-01 | ECLASS 11.0 | 17-13-01-01 |

**Approvals**

Approvals



ROHS

Conform

**Downloads**User Documentation [Manual](#)

## CRIMPFIX LZ

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

