

POWERSTRIPPER 16,0**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

- for automatic stripping of individual wires
- stripping of flexible wires according to DIN VDE 0295, Cl. 5
- Partial stripping of insulation, the isolation remains on wire end
- Change of tools not necessary
- Quick and easy setting for the proper cross-section
- Stripping length from 3 to 20 mm
- Min. conductor length: 22 mm + stripping length
- Electric drive

General ordering data

Version	Tools, Automatic stripper
Order No.	9028480000
Type	POWERSTRIPPER 16,0
GTIN (EAN)	4032248064632
Qty.	1 pc(s).

POWERSTRIPPER 16,0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	295 mm	Depth (inches)	11.614 inch
Height	230 mm	Height (inches)	9.055 inch
Net weight	8,800 g	Weight	11 kg
Width	190 mm	Width (inches)	7.48 inch

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Automatic stripping

Conductor length, min.	22 mm + stripping length		
Connection values	46 VA		
Drive	electrical		
Electrical connection	100-240 V / 50/65 Hz		
Outer diameter of conductor	max.	8 mm	
Pull-off length	3-20 mm		
Pulse time	approx. 1.5 s		
Stripping range	2.5 - 16 mm² (~AWG 14-6)		

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
ECLASS 9.0	17-13-01-01	ECLASS 9.1	17-13-01-02
ECLASS 10.0	17-13-01-02	ECLASS 11.0	17-13-01-01

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	WSCAD
User Documentation	Manual