

CRIMPFIX L

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

General ordering data

Version	Automatic stripper and crimper
Order No.	9028530000
Type	CRIMPFIX L
GTIN (EAN)	4008190942670
Qty.	1 pc(s).

CRIMPFIX L**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	330 mm	Depth (inches)	12.992 inch
Height	460 mm	Height (inches)	18.11 inch
Net weight	34,000 g	Weight	31 kg
Width	390 mm	Width (inches)	15.354 inch

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

PW65 maintenance - automatic stripping/crimping

Compressed-air connection	5 bar	Consumables	loose cable lugs, with plastic collar
Crimping length	8 mm	Drive	Electropneumatic
Electrical connection	100-240 V / 50/65 Hz	Length of wire-end ferrule	14 mm
Pulse time	approx. 1 s	Stripping range	0.5 - 2.5 mm ² (~AWG 20-14)
Wire end ferrules cross-section, max.	2.5 mm ²	Wire end ferrules cross-section, min.	0.5 mm ²

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
ECLASS 9.0	17-13-01-01	ECLASS 9.1	17-13-01-01
ECLASS 10.0	17-13-01-01	ECLASS 11.0	17-13-01-01

Important note

Product information	Old Version 9022650000 – SOT 1: 0.5 mm ² - 1.5 mm ² up to serial number CF L 1789 and CF LS 1475 9022660000 – SOT 2: 1.5 mm ² - 2.5 mm ² up to serial number CF L 1789 and CF LS 1475 New Version 1440540000 – SOT 1: 0.5 mm ² - 1.5 mm ² from serial number CF L 1790 and CF LS 1476 1440550000 – SOT 2: 1.5 mm ² - 2.5 mm ² from serial number CF L 1790 and CF LS 1476
---------------------	--

Approvals

Approvals



ROHS Conform

DownloadsUser Documentation [Manual](#)