

LIR 2,5M3 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² - 2.5 mm ²
Order No.	9200150000
Type	LIR 2,5M3 V
GTIN (EAN)	4032248409778
Qty.	100 pc(s).

LIR 2,5M3 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	6.2 mm	Depth (inches)	0.244 inch
Net weight	0.72 g	Width	20.6 mm
Width (inches)	0.811 inch		

Technical data

Description of article	Insulated ring-cable connector 2.5 mm ² / M3
------------------------	---

Connectors

Conductor cross-section, max.	2.5 mm ²	Conductor cross-section, min.	1.5 mm ²
Connection density (S1)	0.8 mm	Dimension	M 3
Dimension (bolt)	M 3	Identification colour	blue
Inside diameter (d1)	3.2 mm	Insulation	Available
Material/plastic	PVC	Outside diameter (d)	6.4 mm
Plastic collar diameter (D)	4.5 mm	Plastic collar length (b)	11.3 mm

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------