

LIR 2,5M6 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Insulated ring-cable connector made from PVC

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² - 2.5 mm ²
Order No.	9200190000
Type	LIR 2,5M6 V
GTIN (EAN)	4032248410019
Qty.	100 pc(s).

Creation date March 30, 2021 12:49:04 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

LIR 2,5M6 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	6.2 mm	Depth (inches)	0.244 inch
Net weight	1.12 g	Width	27.3 mm
Width (inches)	1.075 inch		

Technical data

Description of article	Insulated ring-cable connector 2.5 mm ² / M6
------------------------	---

Connectors

Conductor cross-section, max.	2.5 mm ²	Conductor cross-section, min.	1.5 mm ²
Connection density (S1)	0.8 mm	Dimension	M 6
Dimension (bolt)	M 6	Identification colour	blue
Inside diameter (d1)	6.4 mm	Insulation	Available
Material/plastic	PVC	Outside diameter (d)	12 mm
Plastic collar diameter (D)	4.5 mm	Plastic collar length (b)	11.3 mm

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

Approvals



ROHS Conform

DownloadsEngineering Data [EPLAN](#)