

LIR 6M4 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 4 mm ² - 6 mm ²
Order No.	9200230000
Type	LIR 6M4 V
GTIN (EAN)	4032248410057
Qty.	100 pc(s).

LIR 6M4 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Depth	8.1 mm	Depth (inches)	0.319 inch
Net weight	1.7 g	Width	27.2 mm
Width (inches)	1.071 inch		

Technical data

Description of article	Insulated ring-cable connector 6.0 mm ² / M4
------------------------	---

Connectors

Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
Connection density (S1)	1 mm	Connection length (l)	22.4 mm
Dimension	M 4	Dimension (bolt)	M 4
Identification colour	yellow	Inside diameter (d1)	4.3 mm
Insulation	Available	Material/plastic	PVC
Outside diameter (d)	9.5 mm	Plastic collar diameter (D)	6.4 mm
Plastic collar length (b)	14.15 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------