

LIP 2,5R12 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated pin-cable connector made from PVC or PC/PA**

- Conventional designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² - 2.5 mm ² , blue
Order No.	9200470000
Type	LIP 2,5R12 V
GTIN (EAN)	4032248410316
Qty.	100 pc(s).

LIP 2,5R12 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	6.2 mm	Depth (inches)	0.244 inch
Net weight	0.61 g	Width	23.3 mm
Width (inches)	0.917 inch		

Technical data

Description of article	Insulated pin-cable connector 2.5 mm ² L=12 mm
------------------------	---

Connectors

Conductor cross-section, max.	2.5 mm ²	Conductor cross-section, min.	1.5 mm ²
Dimension	12.0 mm	Dimension (pin length)	12 mm
Identification colour	blue	Insulation	Available
Length 1 (l1)	22 mm	Material/plastic	PVC
Outside diameter of shaft (d3)	4.7 mm	Plastic collar diameter (D)	4.7 mm
Plastic collar length (b)	10 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------

LIP 2,5R12 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

