

**LIP 6R14 V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Insulated pin-cable connector made from PVC or PC/PA**

- Conventional designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |                                                                                                    |
|------------|----------------------------------------------------------------------------------------------------|
| Version    | cable lug, terminal end, Insulated cable connector, 4 mm <sup>2</sup> - 6 mm <sup>2</sup> , yellow |
| Order No.  | <a href="#">9200480000</a>                                                                         |
| Type       | LIP 6R14 V                                                                                         |
| GTIN (EAN) | 40322484 10323                                                                                     |
| Qty.       | 100 pc(s).                                                                                         |

**LIP 6R14 V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|                |            |                |            |
|----------------|------------|----------------|------------|
| Depth          | 8 mm       | Depth (inches) | 0.315 inch |
| Net weight     | 1.7 g      | Width          | 28.15 mm   |
| Width (inches) | 1.108 inch |                |            |

**Technical data**

|                        |                                                           |
|------------------------|-----------------------------------------------------------|
| Description of article | Insulated pin-cable connector 6.0 mm <sup>2</sup> L=14 mm |
|------------------------|-----------------------------------------------------------|

**Connectors**

|                                |                   |                               |                   |
|--------------------------------|-------------------|-------------------------------|-------------------|
| Conductor cross-section, max.  | 6 mm <sup>2</sup> | Conductor cross-section, min. | 4 mm <sup>2</sup> |
| Dimension                      | 14.0 mm           | Dimension (pin length)        | 14 mm             |
| Identification colour          | yellow            | Insulation                    | Available         |
| Length 1 (l1)                  | 22 mm             | Material/plastic              | PVC               |
| Outside diameter of shaft (d3) | 2.7 mm            | Plastic collar diameter (D)   | 6.6 mm            |
| Plastic collar length (b)      | 13.5 mm           |                               |                   |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ECLASS 9.0  | 27-40-02-92 | ECLASS 9.1  | 27-40-02-12 |
| ECLASS 10.0 | 27-40-02-92 | ECLASS 11.0 | 27-40-02-92 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

## LIP 6R14 V

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

