

**LIF 1,5F288 R****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Insulated tab-connector sleeves made from PVC  
with copper sleeve**

- Commercially available designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |                                                                                               |
|------------|-----------------------------------------------------------------------------------------------|
| Version    | cable lug, terminal end, Insulated cable connector, 0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup> |
| Order No.  | <a href="#">9200520000</a>                                                                    |
| Type       | LIF 1,5F288 R                                                                                 |
| GTIN (EAN) | 4032248410361                                                                                 |
| Qty.       | 100 pc(s).                                                                                    |

## LIF 1,5F288 R

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                |            |
|----------------|------------|----------------|------------|
| Depth          | 5.7 mm     | Depth (inches) | 0.224 inch |
| Net weight     | 0.62 g     | Width          | 18.7 mm    |
| Width (inches) | 0.736 inch |                |            |

## Technical data

|                        |                                                               |
|------------------------|---------------------------------------------------------------|
| Description of article | Insulated tab-connector sleeves 1.5 mm <sup>2</sup> / 2.8x0.8 |
|------------------------|---------------------------------------------------------------|

## Connectors

|                               |                     |                                  |                     |
|-------------------------------|---------------------|----------------------------------|---------------------|
| Conductor cross-section, max. | 1.5 mm <sup>2</sup> | Conductor cross-section, min.    | 0.5 mm <sup>2</sup> |
| Dimension                     | 2.8 x 0.8 mm        | Dimension (flat blade connector) | 2.8 x 0.8 mm        |
| Identification colour         | red                 | Insulation                       | Available           |
| Material/plastic              | PVC                 | Plastic collar diameter (D)      | 4 mm                |
| Plastic collar length (b)     | 10 mm               | Plug-in density (d3)             | 0.8 mm              |
| Plug-in width (d2)            | 2.8 mm              |                                  |                     |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000516    | ETIM 7.0    | EC000516    |
| ECLASS 9.0  | 27-44-03-92 | ECLASS 9.1  | 27-40-02-90 |
| ECLASS 10.0 | 27-44-03-92 | ECLASS 11.0 | 27-44-03-92 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

### LIF 1,5F288 R

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

