

**LID 1,5F4 RF****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Fully-insulated round-plug sleeves made from PVC  
with copper sleeve**

- Commercially available designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| Version    | cable lug, terminal end, Insulated cable connector, 0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup> , red |
| Order No.  | <a href="#">9200700000</a>                                                                          |
| Type       | LID 1,5F4 RF                                                                                        |
| GTIN (EAN) | 4032248410545                                                                                       |
| Qty.       | 100 pc(s).                                                                                          |

## LID 1,5F4 RF

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                |            |
|----------------|------------|----------------|------------|
| Depth          | 7.6 mm     | Depth (inches) | 0.299 inch |
| Net weight     | 1.25 g     | Width          | 23 mm      |
| Width (inches) | 0.906 inch |                |            |

## Technical data

|                        |                                                                |
|------------------------|----------------------------------------------------------------|
| Description of article | Round-plug sleeve with copper sleeve 0.5 - 1.5 mm <sup>2</sup> |
|------------------------|----------------------------------------------------------------|

## Connectors

|                               |                     |                               |                     |
|-------------------------------|---------------------|-------------------------------|---------------------|
| Conductor cross-section, max. | 1.5 mm <sup>2</sup> | Conductor cross-section, min. | 0.5 mm <sup>2</sup> |
| Dimension                     | ø 4 mm              | Dimension (round plug)        | ø 4 mm              |
| Identification colour         | red                 | Insulation                    | Fully insulated     |
| Material/plastic              | PVC                 | Outside diameter (d)          | 4 mm                |
| Plastic collar diameter (D)   | 4 mm                | Plastic collar length (b)     | 10.5 mm             |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ECLASS 9.0  | 27-40-02-12 | ECLASS 9.1  | 27-40-02-12 |
| ECLASS 10.0 | 27-40-02-12 | ECLASS 11.0 | 27-40-02-12 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### LID 1,5F4 RF

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

