


RS031-ODC24/F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**General ordering data**

Version	RS-SERIES, solid-state relays, 1 NO contact (Bipolar transistor), Rated control voltage: 24 V DC $\pm 10\%$, Rated switching voltage: 5...50 V DC, Continuous current: 3 A, Screw connection
Order No.	9430820000
Type	RS031-ODC24/F
GTIN (EAN)	4008190431860
Qty.	20 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2019-04-06
Alternative product	1275100000

Creation date March 30, 2021 1:03:59 AM CEST

RS031-ODC24/F

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	68 mm	Depth (inches)	2.677 inch
Height	80 mm	Height (inches)	3.15 inch
Net weight	40.9 g	Width	12.5 mm
Width (inches)	0.492 inch		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-25 °C...40 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Control side

Nominal control current	11 mA DC	Power rating	0.29 W
Rated control voltage	24 V DC $\pm$ 10 %	Status indicator	red LED

Load side

Continuous current	3 A	Leakage current	$\leq$ 1 mA
Protective circuit, load side	Free-wheeling diode	Short-circuit-proof	No
Voltage drop at max. load	1.6 V	max. switching frequency (DC control voltage)	500 Hz

Contact data

Contact type	1 NO contact (Bipolar transistor)
--------------	-----------------------------------

General data

Rail	TS 32, TS 35	Colour	orange
------	--------------	--------	--------

Insulation coordination

Clearance and creepage distances for control side - load side	$\geq$ 8 mm	Impulse withstand voltage	4 kV
Pollution severity	2	Rated voltage	300 V
Surge voltage category	III		

Further details of approvals / standards

Standards	DIN EN 50178
-----------	--------------

Connection data

Wire connection method	Screw connection	Clamping range, rated connection	2.5 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	2.5 mm ²

RS031-ODC24/F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC001504	ETIM 7.0	EC001504
ECLASS 9.0	27-37-16-04	ECLASS 9.1	27-37-16-04
ECLASS 10.0	27-37-16-04	ECLASS 11.0	27-37-16-04

Approvals

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity[DE_PA_5600_160311_001.pdf](#)

Engineering Data

[EPLAN_WSCAD](#)


RS031-ODC24/F

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Wiring diagram




Schaltsymbol

Dimensional drawing

Recommended spare fuse

Fuses ≤ 4 A (fast characteristic) can be used



Recommended spare fuse: Fuses less than or equal to 4 A (quick-acting) can be used