

## **SAIB-4/7**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

## **General ordering data**

Version	Sockets prefabricated to customer spec., M12, Female socket, straight
Order No.	<u>9457240000</u>
Туре	SAIB-4/7
GTIN (EAN)	4008190312275
Qty.	1 pc(s).



## **SAIB-4/7**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

## **Technical data**

-			
Dim	ensions	and	weights

Net weight 25 g

### **Environmental Product Compliance**

REACH SVHC Lead 7439-92-1,

Imidazolidine-2-thione

96-45-7

#### Technical data customisable plug-in connectors

Cable diameter	46 mm (PG7)/ 68 mm (PG9)	Cable diameter, max.	6 mm
Cable diameter, min.	4 mm	Coding	А
Conductor cross-section, max.	0.75 mm²	Conductor cross-section, min.	0.14 mm <sup>2</sup>
Connection cross-section, max.	0.75 mm <sup>2</sup>	Connection cross-section, min.	0.14 mm <sup>2</sup>
Contact surface	CuSnZn	Housing main material	PA
Insulation strength	10 <sup>8</sup> Ω	Number of poles	4
Plugging cycles	≥ 50	Pollution severity	3
Protection degree	IP67	Rated current	4 A
Rated voltage		Rated voltage (text)	250 V (4-pole) / 60 V (5-
	250 V		pole)
Shield connection	No	Temperature range of housing	-40 +85 ° C
Threaded ring material	Diecast zinc	Type of connection	Screw connection

## **Standards**

Connector standard IEC 61076-2-101

#### Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC002635
ECLASS 9.0	27-44-01-02	ECLASS 9.1	27-44-01-03
ECLASS 10.0	27-44-01-02	ECLASS 11.0	27-44-01-02

#### **Approvals**

Approvals



ROHS	Conform
UL File Number Search	E307231

#### **Downloads**

Engineering Data	<u>STEP</u>	
Engineering Data	EPLAN, WSCAD, Zuken E3.S	
User Documentation	<u>Manual</u>	



## **SAIB-4/7**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Drawings**

### Pole scheme

