

## **SAI-SA-3-IDC**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The IDC is simple and quick to assemble since this technology allows the conductor to be inserted directly into the terminal point, without crimping or having to strip the insulation. It also has excellent functional security.

#### **General ordering data**

Version	Sensor/Actuator plug-in connector, M12, pin, straight
Order No.	<u>9457720000</u>
Туре	SAI-SA-3-IDC
GTIN (EAN)	4032248154869
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

# **SAI-SA-3-IDC**

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

-	-		
Dım	ensions	and	weights

Net weight 13.3 g

#### **Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

# Technical data customisable plug-in connectors

Cable diameter	45.1 mm	Cable diameter, max. 5.1 mm	
Cable diameter, min.	4 mm	Coding	none
Conductor cross-section, max.	0.5 mm <sup>2</sup>	Conductor cross-section, min.	0.25 mm <sup>2</sup>
Connection cross-section, max.	0.5 mm <sup>2</sup>	Connection cross-section, min.	0.25 mm <sup>2</sup>
Contact surface	tinned	Housing main material	CuZn
Insulation strength	10 <sup>8</sup> Ω	Number of poles	3
Plugging cycles	≥ 50	Pollution severity	3
Protection degree	IP67	Rated current	4 A
Rated voltage	32 V	Rated voltage (text)	32 V
Shield connection	No	Temperature range of housing	-25+85 °C
Threaded ring material		Type of connection	Insulation displacement
	Diecast zinc		connection

#### Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC002635
ECLASS 9.0	27-44-01-02	ECLASS 9.1	27-44-01-03
ECLASS 10.0	27-44-01-02	ECLASS 11.0	27-44-01-02

## **Approvals**

Approvals



ROHS Conform

## **Downloads**

User Documentation <u>Manual</u>