

POK MOPL 4040

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Similar to illustration







The Klippon[®] POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

General ordering data

Version	Klippon POK (polyester empty enclosure), Mounting plate, Height: 389 mm, Width: 383 mm,
	Depth: 1.5 mm, Material: Sheet steel, galvanized,
	Miscellaneous, silver
Order No.	<u>9510670000</u>
Туре	POK MOPL 4040
GTIN (EAN)	4008190498313
Qty.	1 pc(s).



POK MOPL 4040

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	1.5 mm	Depth (inches)	0.059 inch
Height	389 mm	Height (inches)	15.315 inch
Mounting dimension - height	250 mm	Mounting dimension - width	372 mm
Net weight	1,770 g	Width	383 mm
Width (inches)	15.079 inch		

Certificate numbers enclosure

Certificate No. (EAC)	RUC-DE.BE02.B.00173	

General information

Material	Sheet steel, galvanized	Material thickness	1.5 mm
Surface finish	Miscellaneous	Type of fixing	when screwed in

Classifications

ETIM 6.0	EC000213	ETIM 7.0	EC000213
ECLASS 9.0	27-40-06-39	ECLASS 9.1	27-18-92-90
ECLASS 10.0	27-40-06-39	ECLASS 11.0	27-40-06-39

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data	<u>STEP</u>
Engineering Data	EPLAN, WSCAD