


WNT 70N/35**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Neutral conductor disconnect terminal, Busbar connection, 70 mm ² , 400 V, 140 A, sliding, blue
Order No.	9512210000
Type	WNT 70N/35
GTIN (EAN)	4008190403898
Qty.	10 pc(s).

WNT 70N/35

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	85 mm	Depth (inches)	3.346 inch
Depth including DIN rail	86 mm	Height	75 mm
Height (inches)	2.953 inch	Net weight	138.4 g
Width	20.5 mm	Width (inches)	0.807 inch

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

Material data

Material	Wemid	Colour	blue
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection, with busbar connection 10x3, in closed state	End cover plate required	No
Number of potentials	1	Number of levels	1
Number of clamping points per level	1	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35	N-function	Yes
PE function	No	PEN function	No

Additional technical data

Explosion-tested version	No	Installation advice	Busbar
Number of similar terminals	1	Open sides	closed
Type of mounting	Snap-on		

Conductors for clamping (additional connection)

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max. 70 mm²

Conductors for clamping (rated connection)

Blade size S6 (DIN 6911)

WNT 70N/35

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Clampable conductor	Connection specification		Screw connection	
	Cross-section for conductor connection	Type	solid, H05(07) V-U	
		min.	10 mm ²	
		max.	16 mm ²	
		nominal	16 mm ²	
	wire end ferrule	Stripping length	min.	22 mm
			max.	22 mm
			nominal	22 mm
		Tightening torque	min.	6 Nm
			max.	12 Nm
		Recommended wire-end ferrule		
	Connection specification		Screw connection	
	Cross-section for conductor connection	Type	stranded, H07V-R	
		min.	10 mm ²	
		max.	95 mm ²	
		nominal	70 mm ²	
	wire end ferrule	Stripping length	min.	22 mm
			max.	22 mm
			nominal	22 mm
		Tightening torque	min.	6 Nm
			max.	12 Nm
		Recommended wire-end ferrule		
	Connection specification		Screw connection	
	Cross-section for conductor connection	Type	flexible, H05(07) V-K	
		min.	10 mm ²	
		max.	70 mm ²	
		nominal	70 mm ²	
wire end ferrule	Stripping length	min.	22 mm	
		max.	22 mm	
		nominal	22 mm	
	Tightening torque	min.	6 Nm	
		max.	12 Nm	
	Recommended wire-end ferrule			
Clamping range, max.	95 mm ²			
Clamping range, min.	10 mm ²			
Clamping screw	M 8			
Connection cross-section, stranded, max.	95 mm ²			
Connection cross-section, stranded, min.	10 mm ²			
Connection direction	on side			
Gauge to IEC 60947-1	B 11			
Number of connections	1			
Stripping length	22 mm			
Tightening torque, max.	12 Nm			
Tightening torque, min.	6 Nm			
Type of connection	Busbar connection			
Wire connection cross section, finely stranded, max.	70 mm ²			
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	70 mm ²			
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	10 mm ²			
Wire connection cross-section, solid core, max.	16 mm ²			

Creation date March 30, 2021 3:16:19 AM CEST

WNT 70N/35

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Wire connection cross-section, solid core, min. 10 mm²

General

Installation advice	Busbar	Rail	TS 35
Standards	In accordance with IEC 60947-7-1		

Rating data

Power loss in accordance with IEC 60947-7-x	6.14 W	Rated cross-section	70 mm ²
Rated voltage	400 V	Rated current	140 A
Current at maximum wires	140 A	Standards	In accordance with IEC 60947-7-1
Volume resistance according to IEC 60947-7-x	0.17 mΩ	Rated impulse withstand voltage	6 kV
Pollution severity	3		

UL rating data

Certificate No. (UR)	E60693	Conductor size Factory wiring max. (UR)	00 AWG
Conductor size Factory wiring min. (UR)	6 AWG	Conductor size Field wiring max. (UR)	00 AWG
Conductor size Field wiring min. (UR)	6 AWG	Current size C (UR)	175 A
UL_current_Print	175 A	UL_voltage_Print	600 V
UL_wire_max_Print	0 AWG	UL_wire_min_Print	6 AWG
Voltage size C (UR)	600 V		

Classifications

ETIM 6.0	EC000902	ETIM 7.0	EC000902
ECLASS 9.0	27-14-11-26	ECLASS 9.1	27-14-11-26
ECLASS 10.0	27-14-11-26	ECLASS 11.0	27-14-11-26

Approvals

Approvals



ROHS	Conform
UL File Number Search	E60693

Downloads

Approval/Certificate/Document of Conformity	EAC certificate Declaration of Conformity Declaration of Conformity
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks

WNT 70N/35

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

