

**DMSI MANUELL 0,5-1,7****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

If you demand effective and exact work, it is essential to use the precise torque. This also guarantees high repetition accuracy.

This is the perfect job for the new Weidmüller torque screwdriver with the ergonomic grip and the unique interchangeable bit system.

- Compact and especially light design
- Torque set with special tool (supplied); an unintended, incorrect setting is ruled out.
- Ergonomic handle sizes matched to the torque range.
- Tools subjected to routine testing and provided with an ID number; 100% quality control with verification and product reference.
- Clicking sound upon reaching the set torque, clearly audible and noticeable, no unnecessary tightening.
- Interchangeable blades made from high-quality wear-resistant tool steel.
- All tools fulfil the accuracy requirements of: EN ISO 6798, BS EN 26789, ASME B107.14M
- Trigger accuracy +/- 6% of the set scale value.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | Torque screwdriver         |
| Order No.  | <a href="#">9918390000</a> |
| Type       | DMSI MANUELL 0,5-1,7       |
| GTIN (EAN) | 4032248388356              |
| Qty.       | 1 pc(s).                   |

**DMSI MANUELL 0,5-1,7**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Technical data****Dimensions and weights**

|            |        |                |            |
|------------|--------|----------------|------------|
| Net weight | 425 g  | Weight         | 190 g      |
| Width      | 200 mm | Width (inches) | 7.874 inch |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Technical data**

|                        |                                              |
|------------------------|----------------------------------------------|
| Description of article | VDE-insulated torque screwdriver, 0.5-1.7 Nm |
|------------------------|----------------------------------------------|

**Screwing tools**

|                      |        |                      |        |
|----------------------|--------|----------------------|--------|
| Torque setting, max. | 1.7 Nm | Torque setting, min. | 0.5 Nm |
|----------------------|--------|----------------------|--------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000149    | ETIM 7.0    | EC000149    |
| ECLASS 9.0  | 21-04-04-07 | ECLASS 9.1  | 21-04-04-90 |
| ECLASS 10.0 | 21-04-50-03 | ECLASS 11.0 | 21-04-50-03 |

**Approvals**

Approvals

**Downloads**

|                                             |                                                        |
|---------------------------------------------|--------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Manufacturer's Declaration - Slim Bits</a> |
|---------------------------------------------|--------------------------------------------------------|

### DMSI MANUELL 0,5-1,7

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Example of use

