

VT CTB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The main function of the voltage tester is to establish if voltage is present. A 2-pole voltage tester is the only approved testing instrument that fulfils the requirements of work protection regulations.

- with LED-Display
- acc. to VDE standard
- high peak voltage strength
- the right tester for every application

General ordering data

Version	Testing tools, 2-pole voltage tester
Order No.	9918970000
Type	VT CTB
GTIN (EAN)	4032248405855
Qty.	1 pc(s).

VT CTB

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	19 mm	Depth (inches)	0.748 inch
Height	21 mm	Height (inches)	0.827 inch
Net weight	50 g	Weight	50 g
Width	137 mm	Width (inches)	5.394 inch

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Description of article	Voltage tester up to 48 V
------------------------	---------------------------

Measuring and testing devices

AC voltage measuring range	3-48 V	Continuity test	No
DC voltage measuring range	48 V	Display	LED
Frequency range, max.	65 Hz	Frequency range, min.	0 Hz
Load switchable	No	Phase sequence display	No
Protection degree	IP40	Rated voltage, max.	48 V DC
Rated voltage, min.	3 V DC	Tested and approved according to	EN 61010-1, EN 61326
Working temperature, max.	50 °C	Working temperature, min.	-10 °C

Classifications

ETIM 6.0	EC000494	ETIM 7.0	EC000494
ECLASS 9.0	27-20-03-08	ECLASS 9.1	27-20-03-08
ECLASS 10.0	27-20-03-08	ECLASS 11.0	27-20-03-08

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

User Documentation	Manual
--------------------	------------------------

VT CTB

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

